

Poster LED display

Innovative, fashionable and intelligent







Poster Led Display Applications













Exhibition

Hotel

Showcase



Bar





Retail Shop

Product Introduction

Features

FUSION excels in:

- Super slim in width and light in weight.
- 20-30mm frame border; 38kg weight, easy to install and move.
- Multiple installation modes, such as stand, wall-mounted and etc.
- Plug-in display, simple operation.
- Multiple linkage modes, such as single display application, cascaded application and creat
- USB/ Wi-Fi/4G/ HDMI / cable connection; mobile phone & PC quick management & publish.
- LAN integrated publish & remote publish via internet.
- Calibration data saved on modules, recover factory settings in 5s.
- •The exterior of the cabinet is equipped with an acrylic plate to protect the screen body.






module size



160mm

320mm

Back










Screen Specifications

Complete size with stand













Stand-alone PC Display Application

Stand-alone PC Display via LAN








External wiring diagram for each CRIUS


multi units connection diagram. Using playing software updates playlist to each display. Each screen also can be controlled and managed via LAN and Internet.

Stand-alone PC Display Application

Single CRIUS played via CLOUD



Multi CRIUS connection diagram




External wiring diagram for each CRIUS


Connect the CRIUS to Internet via Wi-Fi / Cable, log in the cloud platform, remotely control and manage the CRIUS in different regions.



Stand-alone Device Display Application

Stand-alone Device Display Application Via Built-in Player





Control system diagram of single CRIUS

External wiring diagram of single CRIUS

CRIUS system diagram under stand-alone device display working mode.

Playlist can be imported by U disk, network connected computer, PC and cell phone App to built-in processor.



Multi-units Cascade Extended Display Application

(Connected with external HDMI signal)



Control system of 4~6 CRIUS




Indoor poster display Parameters



pixel pitch	P1.8	P2	P2.5	P3
LED Type	SMD1515 SMD2121			
Module Size	320*160mm			
Screen size	640*1600mm/640*1920mm/576*1920mm			
Material	Arcylic+Aluminum			
Cabinet Weight		32kg/pcs		
Control Method	4G.WIFI/Ethernet+Cloud control+APP			
Protection	IP40			
Max Power Consumption	750W			
Ave. Power Consumption		250w/m ²		
Refresh Rate	2880~3840Hz			
Grey Scale	16Bits			
Viewing Angle		H160/V160		
Voltage	AC100~240V(50-63HZ)			
Working Temperature	-40°C+70°C			
Color Temperature		65009500K		
Working Humidity	10%90%RH			
Brightness Sonsor		0-255 level Automatic adjustment,Optional		
Certification	EMC/CE/ROHS/CCC/FCC/ISO			


Poster LED display FUSION

Indoor Series				
pixel pitch	Display size(mm)	Brightness		
1.839	640x1600 / 640x1760 / 640x1920	600		
2	640x1600 / 640x1760 / 640x1920	800		
2.5	640x1600 / 640x1760 / 640x1920	1000		
3	576x1920	800		


















Application Scenario











Contact us:info@signogramkw.com

website: www. signogramkw. com